



BRAVO LIGHTER LED V RD



BRAVO LIGHTER LED V SQ


- A range of recess downlight LED luminaires.
- Die cast aluminium with PS optic, build in driver inside.
- Available in three different bezel sizes 4" to 8" to cater for most applications from 9W to 18W.
- Slim body with high quality diffuser allows for a wider light distribution than a reflector downlight, with increased spacing between luminaires.
- High efficacy up to 100lm/W

PRODUCT OVERVIEW

Technology	LED
Dimmable	No
Compatible dimmers	Non Dimmable
Mount	Recessed to T-bar or conceal ceiling
Housing	Die cast aluminium
CRI (Ra)	80
Colour temperature (K)	3000K, 6500K
Lumen (lm)*	900 / 1200 / 1800
Wattage (W)	9 / 12 / 18W
Voltage (V)	AC 220-240V build-in driver
Surge protection	1.5kV
Lamps	SMD LED's
Life	30,000 hrs
Colour	White
Diffuser	PS diffuser plate

* For Daylight(6500K)

TECHNICAL



Item	Cutout B (mm)	Dimension AxH (mm)
BRAVO LIGHTER LED V RD-9W	135	147x25
BRAVO LIGHTER LED V RD-12W	155	169x25
BRAVO LIGHTER LED V RD-18W	210	222x25
BRAVO LIGHTER LED V SQ-9W	135x135	145x145x25
BRAVO LIGHTER LED V SQ-12W	155x155	167x167x25
BRAVO LIGHTER LED V SQ-18W	204x204	216x216x25